

Key Features:

- Very High Brightness
- Wide Viewing Angle
- High Contrast Ratio
- LVDS
- Long Lamp Life
- LED Backlight
- Thin and Light



LID12A



AD5621



LF/LH1055E (CM G1041X1-L01)

Model No.	LF1055	LH1055
LCD Display	10.4" TFT Active Matrix Panel	10.4" TFT Active Matrix Panel
Brightness	800 cd/m ² (Max 1000cd/m ²)	800 cd/m ² (Max 1000cd/m ²)
Pixel Pitch(mm)	0.2055(H) x 0.2055(V)	0.2055(H) x 0.2055(V)
Max. Resolution	1024x 768 XGA	1024x 768 XGA
Contrast Ratio	800:1	800:1
Display Area	210.4 x 157.8mm	210.4 x 157.8mm
Response Time(Typ.)	40ms(Typ.)	40ms(Typ.)
Display Colors	16.2M colors	16.2M colors
Viewing Angle	+75°~-75°(H), +75°~-75°(V)	+75°~-75°(H), +75°~-75°(V)
Video		RGB Analog 0.7V Peak to Peak
Sync		LVDS
Signal Connector		15 Pin D-sub
F/R Control Button		Power Switch, Menu, Select (+, -), Auto
OSD Menu		Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
S-video / AV connector		optional
Power Consumption	17.4V, 0.8A	17.4V, 0.8A
Dimensions (mm)	272x204.6x13mm	272x204.6x13mm
Weight (Net)	650g	680g
LED Driving Board	LID12	LID12
Control Board		AD5621GA
Operation Temperature	-20°C~60°C	-20°C~60°C