

# Platform Specifications



Platform

## Key Features

- Sunlight Readable
- LED Backlight
- -20°C~60°C Wide Temp.
- Low Power Consumption
- High Shock & Vibration Resistance
- 90% High Uniformity
- Low EMI Noise
- Wide Dimming
- Multiple Mounting Choices
- 70000hrs Life Expectancy



## SLD1555 (CMO G150X1-L02)

<b>Model No.</b>	SLD1555
<b>LCD Display</b>	15" LED Backlight LCD
<b>Display Area</b>	304.128 x 228.096mm
<b>Brightness</b>	1500 cd/m <sup>2</sup>
<b>Resolution</b>	1024 x 768 (XGA)
<b>Contrast Ratio</b>	700 : 1
<b>Pixel Pitch (mm)</b>	0.297(H) x 0.297(V)
<b>Viewing Angle</b>	160°(H), 160°(V)
<b>Display Colors</b>	16,194,277 colors
<b>Response Time</b>	25ms (Typical)
<b>Sync</b>	LVDS x 1 Channel
<b>Power Consumption</b>	30W
<b>LED Driving Board</b>	LI D15A
<b>Control Board (Optional)</b>	AD5621GA (Standard)
<b>F / R Control Button</b>	Power Switch, Menu, Select (+,-), Auto
<b>OSD Menu</b>	Brightness, Contrast, H/V Position, Color, Phase, Clock....
<b>Dimensions (WxHxD)</b>	389x325x61.6mm
<b>Weight</b>	4.62kgs
<b>Optional</b>	<input checked="" type="checkbox"/> Touch Screen

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

<b>Control Board (Optional)</b>	AD5621GA/AD5621GD/AD5766GDVA/AD1501GDV
<input checked="" type="checkbox"/> <b>AD5621GA</b>	VGA+Audio
<input checked="" type="checkbox"/> <b>AD5621GD</b>	VGA+DVI
<input checked="" type="checkbox"/> <b>AD5766GDVA</b>	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
<input checked="" type="checkbox"/> <b>AD1501GDV</b>	VGA+DVI+S-Video
<b>F / R Control Button</b>	5 Key / 4 Key (Optional)
<input checked="" type="checkbox"/> <b>5 Key</b>	Power Switch, Menu, Select (+,-), Auto
<input checked="" type="checkbox"/> <b>4 Key</b>	Power Switch, Menu, Select (+,-)

SLO= Open Frame

SLD= Industrial Casing



