



ABT™

CCFL Specifications

Key Features

- Sunlight Readable
- Wide Viewing Angle
- High Contrast Ratio
- LVDS
- Long Lamp Life
- Fast Response Time
- Thin and Light
- 12 CCFL



ALF/ALH1955 (AUO M190EG02 V4)

Model No.	ALF1955	ALH1955
LCD Display	19" TFT LCD Module	19" TFT LCD Module
Display Area	376.32 x 301.056 mm	376.32 x 301.056 mm
Brightness	1000 cd/m ²	1000 cd/m ²
Resolution	1280x1024 (SXGA)	1280x1024 (SXGA)
Contrast Ratio	800 : 1	800 : 1
Pixel Pitch (mm)	0.294(H) x 0.294(V)	0.294(H) x 0.294(V)
Viewing Angle	+80° ~ -80° (H), +80° ~ -80° (V)	+80° ~ -80° (H), +80° ~ -80° (V)
Display Colors	16.7M colors	16.7M colors
Response Time	5ms (Typical)	5ms (Typical)
Sync	LVDS	LVDS
Power Consumption	54W	59W
Inverter	LI 1219A	LI 1219A
Control Board (Optional)		AD5621GA (Standard)
F / R Control Button		Power Switch, Menu, Select (+,-), Auto
OSD Menu		Brightness, Contrast, H/V Position, Color, Phase, Clock....
Dimensions (WxHxD)	396x324x23.5mm	396x324x23.5mm
Weight	2230g	2330g
Optional	<input checked="" type="checkbox"/> Touch Screen	

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Control Board (Optional)	AD5621GA/AD5621GD/AD5766GDVA/AD1501GDV
<input checked="" type="checkbox"/> AD5621GA	VGA+Audio
<input checked="" type="checkbox"/> AD5621GD	VGA+DVI
<input checked="" type="checkbox"/> AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
<input checked="" type="checkbox"/> AD1501GDV	VGA+DVI+S-Video
F / R Control Button	5 Key / 4 Key (Optional)
<input checked="" type="checkbox"/> 5 Key	Power Switch, Menu, Select (+,-), Auto
<input checked="" type="checkbox"/> 4 Key	Power Switch, Menu, Select (+,-)

ALF= Panel+Inverter

ALH= Panel+Inverter+Control Board






ABT™

CCFL Specifications

Outline Dimensions
unit:mm



- Note :
- 1.Outline Tolerance : 0.5mm
 - 2.Lamp Connector : JST BHR-03VS-1
 - 3.Lamp Cable : U13239 AWG22 L=140±5mm



Enrich your visual world....