

LED B/L Specifications



Key Features

- Sunlight Readable
- LED Backlight
- -20°C~60°C Wide Temp.
- Low Power Consumption
- High Shock & Vibration Resistance
- 90% High Uniformity
- Low EMI Noise
- Wide Dimming
- Multiple Mounting Choices
- 70000hrs Life Expectancy



DLF/DLH0615 (PVIPD064VT4)

Model No.	DLF0615	DLH0615E
LCD Display	6.4" LED Backlight	6.4" LED Backlight
Display Area	129.6 x 97.4 mm	129.6 x 97.4 mm
Brightness	1000 cd/m ²	1000 cd/m ²
Resolution	640 x 480 (VGA)	640 x 480 (VGA)
Contrast Ratio	400 : 1	400 : 1
Pixel Pitch (mm)	0.2025(H) x 0.203(V)	0.2025(H) x 0.203(V)
Viewing Angle	120°(H), 95°(V)	120°(H), 95°(V)
Display Colors	262K colors	262K colors
Response Time	40ms	40ms (Typical)
Sync	TTL	TTL
Power Consumption	11W	16W
LED Driving Board	LI D06A	LI D06A
Control Board (Optional)		AD5621GA (Standard)
F / R Control Button		Power Switch, Menu, Select (+,-), Auto
OSD Menu		Brightness, Contrast, H/V Position, Color, Phase, Clock...
Dimensions (WxHxD)	178.8x126.8x20.4mm	178.8x126.8x20.4mm
Weight	340g	400g
Optional	<input checked="" type="checkbox"/> AOT <input checked="" type="checkbox"/> Touch Screen	

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.



Control Board (Optional)	AD5621GA/AD5621GD/AD5766GDVA/AD1501GDV
<input checked="" type="checkbox"/> AD5621GA	VGA+Audio
<input checked="" type="checkbox"/> AD5621GD	VGA+DVI
<input checked="" type="checkbox"/> AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
<input checked="" type="checkbox"/> AD1501GDV	VGA+DVI+S-Video
F / R Control Button	5 Key / 4 Key (Optional)
<input checked="" type="checkbox"/> 5 Key	Power Switch, Menu, Select (+,-), Auto
<input checked="" type="checkbox"/> 4 Key	Power Switch, Menu, Select (+,-)

DLF= Panel+Driving Board

DLH= Panel+Driving Board+Control Board

