

# DLD1015-V

10.1" TFT LCD, LED Backlight 1000nits, WSVGA

10.1" TFT LCD panel, built-in 1000 nits high bright for sunlight readable LCD display, high transmittance color filter, high transmission polarizing plates, Low Power Consumption, suitable for kiosk, advertising, POS, marline, transportation, gaming, studio display, gas pump.



## KEY FEATURES

- Sunlight Readable
- LED Backlight
- High Shock & Vibration Resistance
- Low Power Consumption
- Wide Operation Temp. (-20°C~70°C)
- High Uniformity
- Low EMI Noise
- Wide Dimming
- Life Expectancy

## SPECIFICATIONS

Model No.	DLD1015-V
Description	10.1" TFT LCD, LED Backlight 1000nits, WSVGA
Display Area (mm)	222.7 x 125.3 mm
Brightness	1000 cd/m <sup>2</sup>
Resolution	1024 x 600 (WSVGA)
Contrast Ratio	900 : 1
Pixel Pitch (mm)	0.2175(H) x 0.2088(V)
Viewing Angle	+80°~-80°(H), +80°~-80°(V)
Display Colors	16.7M
Response Time (Typical)	16ms (Typical)
Sync	LVDS
Operating Temperature	0 °C ~ 50 °C
Storage Temperature	-20 °C ~ 60 °C
Power Consumption (SSF)	6.36W
Dimensions (mm)	244.0(H) X 148.2(V) X 36.5(D) mm
Weight (Net)	0.7kg
LED Driving Board	LID 10A
Control Board (Optional)	<input type="checkbox"/> AD6038G <input type="checkbox"/> AD6038GA
<input type="checkbox"/> AD6038G	VGA
<input type="checkbox"/> AD6038GA	VGA+Audio
F / R Control Button	<input type="checkbox"/> 4 Key
<input type="checkbox"/> 4 Key	Power Switch, Menu, Select (+,-),
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock...
Optional	<input type="checkbox"/> AOT <input type="checkbox"/> Touch Screen

\*Specifications are subject to change without notice. \*\*All brands or product names are trademarks or registered trademarks of their respective companies.

DLD/DLO = Panel+ LED Driving Board + Control Board + Housing

