

DLF1015-I / DLH1015-I

10.1" TFT LCD, LED Backlight 1000nits,1280x800

DLF1015-I / DLH1015-I is 10.1" TFT LCD Module, built-in 1000 nits high brightness, high transmittance color filter, high transmission polarizing plates, lower power consumption, suitable for outdoor tablets, POS and gaming applications.



KEY FEATURES

- 10.1" sunlight readable, high brightness (1,000 nits)
- Resolutions: 1280 x 800
- Industry leading LED backlight
- Aspect ratio of 16:9
- Low power consumption
- BL MTBF: 70,000 hours

SPECIFICATIONS

Model No.	DLF1015-I / DLH1015-I
Description	10.1" TFT LCD, LED Backlight 1000 nits, 1280x800
Display Area (mm)	216.9 (H)×135.6 (V)
Brightness	1000 cd/m ²
Resolution	1280 x 800
Aspect Ratio	16:10
Contrast Ratio	900 : 1
Pixel Pitch (mm)	0.0565 x 0.1695
Viewing Angle	+80°~-80°(H), +80°~-80°(V)
Display Colors	16.7M
Response Time (Typical)	25ms
Power Consumption	6W / 11W
Dimensions (mm)	229.5 x 151.1 x 4.23mm
Weight (Net)	150g
LED Driving Board	LID10A
Control Board (Optional)	<input type="checkbox"/> AD2662GDHM
<input type="checkbox"/> AD2662GDHM	VGA+DVI+HDMI
F / R Control Button	<input type="checkbox"/> 4 Key
<input type="checkbox"/> 4 Key	Power Switch, Menu, Select (+,-),
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock...
Optional	<input type="checkbox"/> AOT <input type="checkbox"/> Touch Screen

*Specifications are subject to change without notice. **All brands or product names are trademarks or registered trademarks of their respective companies.

DLF= Panel+LED Driving Board

DLH= Panel+LED Driving Board+Control Board

MECHANICAL DRAWING Unit: mm

